This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.




F16.1A




F10. 1B




FIC. 2





F16. 3





F164














_







F165




F166




F167








F168




11011







上のゴ



above). Sends barcode information to PC via RS232 communications (D) and turns on external illumination (C) via TTL output (Trigger line PC or Retail Terminal with RS232 input (other communication protocols 2D Barcode Imager with decoder board - reads barcode on license

acceptable).

Ä

Ö


February 11, 2003

www.jadaktech.com P: 888-388-0490 F: 888-411-3688 Liverpool, NY 13088

Hub Promotions

By: Jeffrey Pine

225 Greenfield Parkway Suite 106



10 TH

